

3000 Series DVR

Simple, rugged, compact mobile DVR with big-system functionality



OVERVIEW

The MobileView® 3000 Series Digital Video Recorder is a high-quality, on-board digital video recording system designed for transit vehicles requiring twelve (12) cameras or less. This small, easy-to-use DVR includes standard features that are normally found in more complex systems: up to 240 fps across all channels, picture resolutions up to 4CIF (704x480), dual-stream recording for low-bandwidth video playback, integrated 802.11 AN, BGN wireless for automatic upload of surveillance data, and twelve (12) digital inputs.

The MobileView 3000 Series DVR is designed with installation efficiency in mind. Quick connect wire harnesses with standardized connectors streamline installation. A Web browser interface simplifies configuration without the use of additional software. The removable media caddy allows the user to swap caddies for remote video viewing and retrieval through a docking station providing flexibility when not used with a wireless infrastructure.

STANDARD FEATURES

- 4, 8 or 12 channel models
- 120/240 fps (240/480 ips)
- H.264 encoding
- Dual-stream recording for low-bandwidth recording and playback
- 2 TB interchangeable, locking media caddy
- Resolution configurable by channel (QCIF, CIF, 2CIF, 4CIF)
- Up to 12 audio channels (model dependent)
- 12 Digital inputs
- 2 Relay outputs
- Integrated 802.11 AN, BGN wireless client
- 6 Status LED's on front of DVR
- Multiplex video output
- Standardized wiring harness
- Browser-based programming and configuration
- J1455 compliant for shock and vibration
- J1939 compatible with external module

3000 Series DVR

Simple, rugged, compact mobile DVR
with big-system functionality

Specifications

Video Surveillance

Linux OS	Stable OS Platform, increased compatibility with peripheral devices
Camera Channels	4, 8 or 12 channel models (NTSC/PAL Selectable)
Camera Frame Rate	120/240 frames (240/480 images) per second, max.
Video Streams	Dual streams per channel (Main & Alternate)
Recording Resolution	Main: QCIF, CIF, 2CIF, 4CIF, Alternate: QCIF and CIF
Compression Levels	H.264 compression methods. Configurable individually per input
Video Outputs	1 Multiplex (1UP, 4UP, 6UP*, 8UP*) *6 & 8 on 8/12CH only
Audio Inputs	2 Main plus per channel audio support up to 12 channels
Audio Outputs	1 Mono
Ethernet Ports	Two, 10/100 Mbps
Geo-Location	Enabled by GPS accessory module
Clock & Synchronization	Automatic via GPS or Network time server
Storage Solution	Interchangeable media caddy
Video Download	Download using remote software client
Field Upgrade	Upgrade using remote software client

Monitored Inputs & Outputs

Digital Inputs	Twelve programmable for Open or Closed operation
Digital Outputs	Two for system status monitoring
Relay Outputs	Two Form C, Dry Contact
Delayed Startup	0-120 seconds
Delayed Shutdown	0-99 Minutes

Networking & Communications

Standard Protocols	DHCP, NTP, IPv4
Wireless	802.11 AN, BGN Wireless Client
Wireless Security	WEP, WPA 1 & 2 Personal Mode, AES
Serial Interfaces	RS232, RS45

Electrical & Environmental

Input Power	Vehicle based 12V or 24V DC Nominal (9-32V DC)
Power Consumption	75 Watt Operating, 5W Standby
Output Power	12VDC, 4 Amp Max Load
Operating Shock	Tested per SAE-J1455 section 4.11.3.4
Operating Vibration	Tested per SAE-J1455 section 4.10.4.2

Ambient Specifications

Operation Temperature	14°F to 122°F (-10°C to 50 °C)
Storage Temperature	-4°F to 158°F (-20°C to 70 °C)


Mechanical

Unit Dimensions (L x D x H)	14.75 x 10.5 x 4.0 in. without rear panel shield 14.75 x 13.25 x 4.0 in. with rear panel shield
Caddy Removal	8" space in front of DVR
IP Rating	IP43 with wire shield
Unit Weight	13 lbs.

Regulatory

FCC	Part 15, Class A
-----	------------------

Dimensional Diagrams



Ordering Information

Digital Video Recorder Kits

MVH-4350-04-K1	MobileView® 3004 4 CH DVR with Mounting Plates, J1-J8 Harnesses and Harness Connection Kit (without HDD Kit)
MVH-4350-08-K1	MobileView 3008 8 CH DVR with Mounting Plates, J1-J8 Harnesses and Harness Connection Kit (without HDD Kit)
MVH-4350-12-K1	MobileView 3012 12 CH DVR with Mounting Plates, J1-J8 Harnesses and Harness Connection Kit (without HDD Kit)
MVH-1002-K2-1S	MobileView 3000, 1TB Flex Drive Kit (Caddy and 1TB 2.5 inch SATA SSD)
MVH-1002-K3-20	MobileView 3000, 2TB Flex Drive Kit (Caddy and 2TB 3.5 inch SATA HDD)

DVR Accessories

MVH-4004-00-00	Docking Station with 2 Keys
MVH-3301-M0-04	GPS Module and Antenna, 15' Cable
MVH-7100-00-08	Acceleration and Impact Sensor

DVR Components

MVH-4350-04-01	MobileView 3004 4 CH, DVR Only
MVH-4350-08-01	MobileView 3008 8 CH, DVR Only
MVH-4350-12-01	MobileView 3012 12 CH, DVR Only
MVH-4002A300	Rear Panel Shield
MVH-4002A304	Replacement Vibration Mounts (New Rubber and Brackets), 1 Pair
MVH-4002A310	Mounting Plate with Vibration Mounts (Includes MVH-4002A304)
MVH-1002-01-00	Flex Drive Caddy, 2 Keys, without HDD
MVH-1001-02-1S	MobileView 3000, SATA SSD, 1TB, 2.5 inch, without Caddy
MVH-1002-03-20	SATA HDD, 2TB, 3.5 inch, without Caddy
MVH-1002-KY-00	Key Set (2 each) for DVR Door and HDD Caddy

DVR Cable Harness

MVH-4039-00-00	Harness Connection Kit
MVH-4037-J1-00	Power Harness
MVH-4037-J2-00E	Audio, Status, Accel., J6-12E Harness
MVH-4037-J3-00	Digital Input Harness
MVH-4037-J5-00	Relay Output Harness
MVH-4037-J6-04A	4 CH Video-Audio Input, Power Harness
MVH-4037-J6-08A	8 CH Video-Audio Input, Power Harness
MVH-4037-J6-12EA	12 CH Video-Audio Input, Power Ext. Harness
MVH-4037-J7-00	Audio Output Harness, 15 in. Cable



interlogix.com/mobileview

Specifications subject to change without notice.

All rights reserved.
© 2014 United Technologies Corporation.

401-3782 2014/11 (80140)